

Power supplies

red-y compact series


Supply variations:



Lithium battery (see typecode)

Lithium battery for *red-y compact meter GSM* and *red-y compact regulator GCR*
Lifetime about 2 years with consistent flow

Remark: It is recommended to change the battery within 2 months after 'Low Batt' appears on the instrument's display.



Cable with loose ends for external supply 24 Vdc (see typecode)

Cable for external supply 24 Vdc for *red-y compact meter GCM*, *compact regulator GCR*, *compact switch GCS* and *compact all-in GCA*
8 way cable, length 2.0 m with loose ends



External supply with plug (Euro-Version) – Art.-N° 328-2172

External supply with 230 Vac/24 Vdc for *red-y compact meter GCM*, *compact regulator GCR*, *compact switch GCS* und *compact all-in GCA*
Cable length 3.5 m


Replacement battery module & modification-sets:



Lithium battery – Art.-N° 328-2211

Replacement battery for *red-y compact meter GSM* and *red-y compact regulator GCR*
Lifetime about 2 years with consistent flow


Remark: It is recommended to change the battery within 2 months after 'Low Batt' appears on the instrument's display.



Cable with loose ends – Art.-N° 328-2181 (2m) or 328-2182 (5m)

Modification-set to replace the battery by a cable with loose ends for external supply
8 way cable with loose ends
Art.-N° 328-2181: length 2.0 m/Art.-N° 328-2182: length 5.0 m

Remark: Will be delivered with mounting instruction.



External supply with plug device (Euro-Version) – Art.-N° 328-2172 + 328-2181

Modification-set to replace the battery or the cable with loose ends with an external supply with plug 230 Vac / 24 Vdc, Cable length 3.5 m

Remark: Will be delivered with mounting instruction.

